

SURAVA Box

Vertical awning

VA2100

VA2300

Product data sheet



Product features

- Part of the SURAVA range: one of three premium options for vertical shading – maximum flexibility of use and consistent design
- Shaded area VA2100 up to 20 m², VA2300 up to 25 m²
- Very slim protective box design – rounded or square
- Fabric guide: Wire-rope or rod guide, guide rail 1- or 2-piece rail with or without ZIP system
No chink of light between fabric and rail
- Recessed wire-rope guide for a discreet appearance along columns and posts

Dimensions

- VA2100: Width min. 40 cm, max. 500 cm
Projection min. 40 cm, max. 400 cm
- VA2300: Width min. 40 cm, max. 500 cm
Projection min. 40 cm, max. 500 cm

Installation method

- Installation on the wall
- Installation under the ceiling
- In-reveal installation

Wind resistance

- Beaufort 6 (49.5 km/h)
The wind resistance class may vary depending on the design and dimensions

Drive system / control

- Motor drive
- Operation optionally via wired switch, radio remote control, smart-home systems (e.g. KNX, TaHoma)
- Optional automatic system with sun, wind and rain sensor

Frame colours

- STOBAG Classic Colours C10 (RAL 9016), C12 (RAL 9010), C28 (RAL 9006), C30 (RAL 9007), C34 (DB703), C48 (RAL 7022), C50 (RAL 7016), C52 (RAL 9005)
- Optional colours: Lifestyle (matt and textured) and Rainbow

Fabric

- Acrylic and Oeko Weave
- Soltis Perform 86
- Soltis Perform 92
- Soltis Blockout B92
- Soltis Veozip
- Screens 1%
- Screens 5%
- Twilight

Certificates / Awards



EN 13561



reddot winner 2023

Warranty

- 5 years
Manufacturer's warranty 2 years, with the option to extend by an additional 3 years

B

min. 44
max. $\frac{1}{3} B$

60
10 20 20 10 12.2
27.5
109.5
82
13
9
95.5
3
10.25

108
2
105
36
110
A

D1 - D1

50

25

D2 - D2

D3 - D3

108

105

0

D1

D2

D3

50

B

31.5

min. 44
max. $\frac{1}{3} B$

min. 100
 $\frac{1}{3} B =$
max. 1000

B

31.5

min. 44
max. $\frac{1}{3} B$

min. 100
 $\frac{1}{4} B =$
max. 1000

Technical drawing of the VA241-1 door profile. The drawing includes a top view and a side view, along with a detailed inset of the internal structure.

Top View Dimensions:

- Total width: B
- Section width (left): $\min. 54 \max. 1/3 B$
- Section width (right): $\min. 54 \max. 1/3 B$
- Profile type: VA241-1

Side View Dimensions:

- Height: 136
- Bottom flange height: $\min. 6 \max. 8$

Internal Structure Dimensions (Inset):

- Overall width: 80
- Segment widths: 15, 25, 25, 15
- Overall height: 105
- Internal height: 31
- Internal width: 17
- Internal height: 120
- Internal width: 14.2
- Internal width: 12.55

Digital version – 2026-09 – © STOBAG – Subject to change. Depending on the country or region, the technical details, scope of delivery, guarantee conditions, design and availability may differ from the specifications contained in this document.