

**TENDABOX BX3000**

One-piece U-shaped protective cover (Dimension 179 x 145 mm), as from 500 cm total width protective cover inner reinforcement (Dimension 179 x 145 mm), of extruded aluminium profile as support element of structure with a groove at the upper end of profile for inserting sealing brush. Side cover as cassette end for accepting fabric roller shaft  $\varnothing$  78 or  $\varnothing$  85 of galvanised steel and for securing folding arms. Securing flange (on side cover) with hooks for hanging the awning on the brackets used for wall or ceiling installation. Securing flange, side cover, bracket are all made of aluminium casting alloy. Awning is extended and retracted manually via a bevel gearbox with integrated end stop and freewheel operating handle ring, speed reduction 4.6:1. The bevel gearbox is operated via a removable crank shaft of powder-coated metal in white, grey or black with hook and plastic handle. Front rail of extruded aluminium in rounded (Dimension 98 x 131 mm) or square (Dimension 98 x 131 mm) shape with matching plastic end caps. Folding arms with inverse incline of aluminium extruded profiles and precision parts of aluminium cast alloy, internal tension springs and double stainless steel cables and cable protector over the middle joint. Simple and continuous inclination angle adjustment via a hexagon socket screw in the mounting flange from 0° – 25° with gear and 0° – 85° with motor for wall mounting, 0° – 30° with gear and 0° – 85° with motor for ceiling and rafter mounting.

The aluminium profiles and aluminium cast parts are powder-coated in facade quality. All visible screws are stainless steel. The cover with a spin-dyed acrylic cloth (price category 1), colour consistent, very high UV protection, good tensile strength, water and dirt resistant is from the STOBAG collection.

**Options****Brackets**

In order to cater for different installation conditions such as poor brickwork, wood / steel structures, rafters etc., we offer a range of different types of brackets.

**Wall junction profile**

Aluminium extruded wall junction profile incl. side cover of aluminium sheet is attached to the facade to prevent rainwater dropping between the facade and the awning.

**Roller shaft screen**

Extruded aluminium profile as roller shaft screen.

**Volant-Plus**

Volant-Plus is a drop profile with integrated roller shaft, fabric and declining profile. The fabric can be lowered with a gear and crank.

**Electric drive**

With an electronic limit switch: Tubular AC motor 230 V, 50 Hz or 120 V, 60 Hz (according to the country) with electromechanical brakes and electronic end stop. Thermal protection, protection class IP54 (spray water), with 50 – 150 cm connection cable.

Remote control motor with an electronic limit switch: Tubular AC motor 230 V, 50 Hz or 120 V, 60 Hz (according to the country) with electromechanical brakes and electronic end stop. Integrated radio receiver, thermal protection, protection class IP54 (spray water), with 50 – 150 cm connection cable.

**Cover / manufacture technology**

Awning covers of polyester, acrylic etc. and various assembly technologies such as gluing, TENARA stitching etc. as per STOBAG collection (collection index).