

AIROMATIC PS4500

Awning for conservatories with motor drive. Fabric cover. Box: extruded aluminium profiles, in one piece, round execution, as a construction support element. Side caps in aluminium casting with plug-in gudgeon links to the guide rails and to the roller tube bearing or the motor bearing. Roller tube made of galvanised steel with groove for the cover fixation. Front rail made of extruded aluminium chamber profile, with grooves for the cover and the driver of the pull and push mechanism. With rolled in front rail, the box is completely closed. Guide rails made of extruded aluminium profiles, with slide groove for the plastic gliders, hollow chamber for the integrated gas-filled strut mechanism and stainless steel cable tension system for the cover transport as well as profile groove for the fixation. Fixation made of aluminium casting for individual installations as well as for installations side by side.

Awnings with an extension of more than 300 cm are fitted with one guiding roller profile and more than 500 cm with two, including guiding roller supports for the cover supports. Guiding roller profile is oval extruded aluminium, guide rail fixings are cast aluminium alloy. All visible screws in stainless steel.

Drive

Tubular motor with electronic limit switch and integrated radio receiver (RTS). 120 VAC 60 Hz, with electromechanical brake and thermal protection, Index Protection Rating IP44(Water protection), with 3 wire/ conductor cable.